

AUTO 系列自动泵系统

SERIES AUTOMATIC BOOSTER SYSTEM



The automatic booster systems consist of a JET water pump, a pressure tank, an airtight pressure switch, a pressure gauge and a connecting flexible pipe. make the pump automatic more convenient to use. The pressure tank, equipped with a non-toxic rubber membrane, has been pre-filled with air pressure of approx 0.12 MPa before leaving the factory. These systems give suitable mains water pressure as required by modern domestic applications and industrial applications, and will ensure enough water to supply all user outlets. Most of the pumps included in our range of products can actually be used to form automatic booster systems.

AUTO系列自动供水系统由射流泵，压力罐，压力开关，压力表和一条软管组成，使用十分方便。压力罐内装有一个无毒的橡胶隔膜，出厂前已预注了0.12MPa压力的气体。适用于增加城市和工业的供水压力，代替水塔从而实现自动供水并将确保所有用户足够的水供应。本公司大多数的电泵都可以组成自动供水系统。

WORKING CONDITIONS

- Max Temperature of Fluid up to +40°C
- Max Pressure 10bar
- Max Ambient Temperature up to 40°C

工作条件：

- 最高流体温度为40°C
- 最大可承受的压力10bar
- 最高环境温度40°C

技术参数 TECHNICAL DATA AT 220~240V/50Hz

型号 TYPE	输入功率 Input Power		电流 Current (A)	最大流量 Q.max (l/min)	最高扬程 H.max (m)	最大吸程 Such.max (m)	转速 Speed (r/min)	压力开关 Pressure Switch		总扬程 Total head(m)	流量 Capacity(l/min)								
	KW	HP						开 ON	关 OFF		0	10	20	25	30	35	40	50	
AUTOSP-60	0.37	1/2	2.6	42	35	9	2850	1.4 Bar	2.6 Bar	35	35	30	25	23	20.5	17	4		
AUTOSP-80	0.55	3/4	3.6	46	40	9					40	35	30	28	26	24	19		
AUTOSP-100	0.75	1	4.8	52	45	9					45	39	35	32	30	28	26	6	
AUTOJET-60S	0.37	1/2	2.6	40	35	9					35	30	25	23	20.5	17	4		
AUTOJET-80S	0.55	3/4	3.6	45	40	9					40	35	30	28	26	24	19		
AUTOJET-100S	0.75	1	4.8	50	45	9					45	39	35	32	30	28	26	5	

Note: 110V/60Hz, 115V/60Hz, 127V/60Hz, 110/220V/60Hz, 380V/50Hz ets. Models are available on request
备注: 可以按要求生产110V/60Hz, 115V/60Hz, 127V/60Hz, 110/220V/60Hz等电压频率